## NSN 5955-01-315-2898

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-315-2898

Overall Length:
1.680 inches
Overall Height:
0.500 inches
Overall Width:
0.670 inches
Environmental Protection:
General purpose
Vibration Resistance Range In Hertz:
+20.0/+2000.0
Vibration Resistance Amplitude:
10.0 gravitational units
Shock Resistance Rating In Gravitational Units:
100.0
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
60.0 gigahertz operating channel
Average Power Rating Per Channel:
10.0 milliwatts output
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Solder stud front and receptacle, coaxial rear
Connection Contact Type And Quantity:
2 solder stud external and 1 receptacle, coaxial internal
External Dc Operating Voltage In Volts:
15.0 single voltage
Shelf Life:

N/a

## NSN 5955-01-315-2898

Crystal Controlled Oscillator - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A32200