Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-317-9390

Overall Length:	
0.887 inches	
Overall Height:	
0.400 inches	
Overall Width:	
0.540 inches	
Environmental Protec	tion:
Moisture proof	
Operating Tempuratur	re Range:
-20.0/+70.0 degrees ce	Isius
Storage Tempurature	Range:
-62.0/+125.0 degrees c	elsius
Average Life Measure	ment:
Not rated	
Basic Shape Style:	
Rectangular or square	
Inclosure Type:	
Hermetically sealed	
Operating Control Me	ihod:
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction 1	уре:
Solid state	
Frequency Per Chann	el:
2.0 megahertz operatir	ig channel
Connection Type And	Location:
Err-060 glad hand quicl	disconnect
Connection Contact T	ype And Quantity:
14 liters of liquid nitroge	in drain
External Dc Operating	Voltage In Volts:
4.5 single voltage and	5.5 single voltage
Test Data Document:	
81349-mil-o-55310 spe	cification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes comm	nercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and perfe	ormance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:	
81349-mil-o-55310/16 g	government specification
Shelf Life:	
N/a	

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200