## NSN 5955-01-328-1782

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-328-1782

Overall Length:
0.887 inches
Overall Height:
0.400 inches
Overall Width:
0.540 inches
Environmental Protection:
Moisture proof
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
24.0 megahertz operating channel
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
14 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
4.75 single voltage and 5.25 single voltage
Special Features:
height includes 0.200 in. Pin length
Test Data Document:
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-o-55310/8 government specification
Shelf Life:

N/a

## NSN 5955-01-328-1782

Crystal Controlled Oscillator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200