NSN 5955-01-329-7793

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-329-7793 **Overall Length:** 0.820 inches **Overall Height:** 0.495 inches **Overall Width:** 0.520 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+2000.0 **Shock Resistance Rating In Gravitational Units:** 3000.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 3.579 megahertz operating channel **Shock Pulse Duration Time:** 0.35 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external **External Dc Operating Voltage In Volts:** 5.0 single voltage Shelf Life:

N/a

NSN 5955-01-329-7793

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200