Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-330-7334

Overall Length: Between 0.800 inches and 0.820 inches Overall Height: Between 0.430 inches and 0.470 inches Overall Width: Between 0.500 inches and 0.520 inches Environmental Protection: Moisture proof and shock resistant and vibration Vibration Resistance Range In Hertz: +20.0/+2000.0 Vibration Resistance Amplitude: 20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

1500.0

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

24.72 megahertz operating channel

Shock Pulse Duration Time:

0.5 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

4 pin external

External Dc Operating Voltage In Volts:

4.75 single voltage and 5.25 single voltage

NSN 5955-01-330-7334

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200