Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-331-7912

| Overall Length: | |
|---|------------------|
| 0.887 inches | |
| Overall Height: | |
| 0.400 inches | |
| Overall Width: | |
| 0.540 inches | |
| Environmental Protection: | |
| Moisture proof | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -62.0/+125.0 degrees celsius | |
| Average Life Measurement: | |
| Not rated | |
| Basic Shape Style: | |
| Rectangular or square | |
| Inclosure Type: | |
| Hermetically sealed | |
| Operating Control Method: | |
| Automatic | |
| Installation Design: | |
| Module | |
| Control Type: | |
| Remote | |
| Circuit Construction Type: | |
| Solid state | |
| Frequency Per Channel: | |
| 1.024 megahertz operating channel | |
| Connection Type And Location: | |
| Err-060 glad hand quick disconnect | |
| Connection Contact Type And Quantity: | |
| 14 liters of liquid nitrogen drain | |
| External Dc Operating Voltage In Volts: | |
| 4.5 single voltage and 5.5 single voltage | |
| Test Data Document: | |
| 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data | in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data of | on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Specification Data: | |
| 81349-mil-o-55310/16 government specification | |
| Shelf Life: | |
| N/a | |
| | |

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200