Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-336-5559

Our well to a sub-
Overall Length:
2.000 inches
Overall Height:
1.030 inches
Overall Width:
2.000 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Simulator, airborne jammer an/alt-4 (v)
Basic Shape Style:
Rectangular or square
Identification Designator:
Co-252f16-k at 5.12mhz-27802
Inclosure Type:
Hermetically sealed
Operating Control Method:
Manual
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
5.12 megahertz operating channel
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
5 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
15.0 single voltage
Shelf Life:
N/a
Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200