Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-336-7008

Overall Length:		
0.887 inches		
Overall Height:		
0.620 inches		
Overall Width:		
0.540 inches		
Environmental Protection:		
Moisture proof		
Operating Tempurature Range:		
-28.0/+85.0 degrees celsius		
Storage Tempurature Range:		
-62.0/+85.0 degrees celsius		
Average Life Measurement:		
Not rated		
End Application:		
Tactical air operations, module an/tyq-2 (v) 1		
Basic Shape Style:		
Rectangular or square		
Identification Designator:		
841678-1-13973		
Maximum Operating Altitude Rating:		
12000.0 feet		
Inclosure Type:		
Hermetically sealed		
Operating Control Method:		
Automatic		
Installation Design:		
Module		
Control Type:		
Remote		
Circuit Construction Type:		
Solid state		
Frequency Per Channel:		
22.0689 megahertz operating channel		
Connection Type And Location:		
Err-060 glad hand quick disconnect		
Connection Contact Type And Quantity:		
14 liters of liquid nitrogen drain		
External Dc Operating Voltage In Volts:		
4.75 single voltage and 5.25 single voltage		
Shelf Life:		
N/a		

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200