

View Online at <https://aerobasegroup.com/nsn/5955-01-336-9145>

Overall Length:

0.887 inches

Overall Height:

0.400 inches

Overall Width:

0.540 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Vibration Resistance Amplitude:

20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

30.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+135.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

7.9872 megahertz operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Err-060 glad hand quick disconnect

Connection Contact Type And Quantity:

14 liters of liquid nitrogen drain

External Dc Operating Voltage In Volts:

4.75 single voltage and 5.25 single voltage

Criticality Code Justification:

Feat

Special Features:

Electrostatic sensitive device

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200