Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-339-8264

Overall Length:
0.875 inches
Overall Height:
Between 0.400 inches and 0.450 inches
Overall Width:
Between 0.495 inches and 0.505 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Vibration Resistance Amplitude:
50.0 gravitational units
Shock Resistance Rating In Gravitational Units:
1000.0
Operating Tempurature Range:
-30.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
T-242-400.0khz-57051
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
400.0 kilohertz operating channel
Shock Pulse Duration Time:
1.0 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

5.0 single voltage and 12.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200