Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-346-1886

| Overall Length:   |
|---|
| 0.887 inches  |
| Overall Height:   |
| 0.400 inches  |
| Overall Width:  |
| 0.540 inches  |
| Environmental Protection:   |
| Moisture proof  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Average Life Measurement:   |
| Not rated   |
| Basic Shape Style:  |
| Rectangular or square   |
| Inclosure Type:   |
| Hermetically sealed   |
| Operating Control Method:   |
| Automatic   |
| Installation Design:  |
| Module  |
| Control Type:   |
| Remote  |
| Circuit Construction Type:  |
| Solid state   |
| Frequency Per Channel:  |
| 5.0176 megahertz operating channel  |
| Connection Type And Location:   |
| Err-060 glad hand quick disconnect  |
| Connection Contact Type And Quantity:   |
| 14 liters of liquid nitrogen drain  |
| External Dc Operating Voltage In Volts:   |
| 4.5 single voltage and 5.5 single voltage   |
| Test Data Document:   |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Specification Data:   |
| 81349-mil-c-3098/16 government specification  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
|   |

## NSN 5955-01-346-1886

Crystal Controlled Oscillator - Page 2 of 2

**Fiig:** A32200

