NSN 5955-01-347-0568

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-01-347-0568



Overall Length: 0.815 inches **Overall Height:** 0.363 inches **Overall Width:** 0.515 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** M1160-2.5000mhz-08111 **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 2.5 megahertz operating channel **Shock Pulse Duration Time:** 0.35 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external

NSN 5955-01-347-0568

Crystal Controlled Oscillator - Page 2 of 2



External Dc (perating	Voltage	In Volts:

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200