## NSN 5955-01-350-1250

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-350-1250 **Overall Length:** 0.900 inches **Overall Height:** 0.380 inches **Overall Width:** 0.530 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** H950090-001b-82577 **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 14.175 megahertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 14 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Criticality Code Justification:** Feat **Special Features:** Electrostatic sensitive device

Precious Material And Location: Lead surfaces gold

## NSN 5955-01-350-1250

Crystal Controlled Oscillator - Page 2 of 2



Preci	ious	Mat	teri	al:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200