## NSN 5955-01-350-1251

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-350-1251 **Overall Length:** 0.760 inches **Overall Diameter:** 0.390 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Cylindrical **Identification Designator:** H959042-001b-82577 **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state **Frequency Per Channel:** 1.024 megahertz operating channel **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 3 pin external **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Criticality Code Justification:** 

Feat **Special Features:** Electrostatic sensitive device **Precious Material And Location:** Lead surfaces gold **Precious Material:** Gold

## NSN 5955-01-350-1251

Crystal Controlled Oscillator - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200