

View Online at <https://aerobasegroup.com/nsn/5955-01-350-3703>

**Overall Length:**

Between 0.220 inches and 0.265 inches

**Terminal Length:**

Between 0.500 inches and 0.830 inches

**Diameter:**

Between 0.310 inches and 0.340 inches

**Overall Diameter:**

0.420 inches

**Terminal Diameter:**

Between 0.016 inches and 0.020 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

Between 20.0 and 24.0

**Shunt Capacitance In Picofarads:**

4.0

**Specified Frequency:**

16.000000 megahertz

**Holder Cover Material:**

Metal or glass

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Center To Center Distance Between Terminals:**

0.200 inches

**Drive Level Rating:**

Between 0.1 milliwatts and 0.3 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.004/+0.004 and -0.007/+0.007

**Equivalent Resistance Value In Ohms:**

30.0

**Precious Material And Location:**

External surfaces gold

**Precious Material:**

Gold or platinum

**Style Designator:**

Hat type, 3 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A059a0