

View Online at <https://aerobasegroup.com/nsn/5955-01-350-3703>

Overall Length:

Between 0.220 inches and 0.265 inches

Terminal Length:

Between 0.500 inches and 0.830 inches

Diameter:

Between 0.310 inches and 0.340 inches

Overall Diameter:

0.420 inches

Terminal Diameter:

Between 0.016 inches and 0.020 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 20.0 and 24.0

Shunt Capacitance In Picofarads:

4.0

Specified Frequency:

16.000000 megahertz

Holder Cover Material:

Metal or glass

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Center To Center Distance Between Terminals:

0.200 inches

Drive Level Rating:

Between 0.1 milliwatts and 0.3 milliwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.004/+0.004 and -0.007/+0.007

Equivalent Resistance Value In Ohms:

30.0

Precious Material And Location:

External surfaces gold

Precious Material:

Gold or platinum

Style Designator:

Hat type, 3 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A059a0