Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-354-3851

	-
0.887 inc	
Overall F	-
0.400 inc	
Overall V	
0.540 inc	
-	g Tempurature Range:
	5.0 degrees celsius
-	Fempurature Range:
	5.0 degrees celsius
-	Life Measurement:
Not rated	
	ape Style:
•	lar or square
Inclosure	
	ally sealed
Operatin	g Control Method:
Automatio	
Installati	on Design:
Module	
Control 1	уре:
Remote	
Circuit C	onstruction Type:
Solid stat	e
Frequence	cy Per Channel:
24.5892 r	negahertz operating channel
Connecti	on Type And Location:
Err-060 g	ad hand quick disconnect
Connecti	on Contact Type And Quantity:
14 liters of	f liquid nitrogen drain
External	Dc Operating Voltage In Volts:
4.5 single	e voltage and 5.5 single voltage
Test Data	a Document:
81349-mi	-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; e	xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environm	ental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specifica	tion Data:
81349-mi	-o-55310/14 government specification
Shelf Life	
N/a	
Unit Of M	leasure:
Demilitar	ization:
Yes - den	nil/mli

NSN 5955-01-354-3851

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

