

View Online at https://aerobasegroup.com/nsn/5955-01-355-5496

a. 300 inches Overall Height: 1.000 inches Overall Width: 1.250 inches Operating Tempurature Range: 3.00471.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type Autocation: Receptacle, coaxial external and solder lug external External De Operating Voltage In Volts: 24.0 single voltage Shelf Life: Na Unit Measure: 	view Online at https://aerobasegroup.com/nsn/5955-01-555-5496	
Overall Height: 1.000 inches Overall Width: 1.250 inches Operating Tempurature Range: :30.0/+71.0 degrees celsius Avarage Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Quantity: 1 receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External De Operating Voltage In Volts: 2.4.0 single voltage Shift Life: Na Unit Of Measure: - Demilitarization: - Demilitarization: -	Overall Length:	
1.000 inches Overall Width: 1.250 inches Operating Tempurature Range: -30.04/71.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial stermal and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Sheft Life: Na Unit Of Measure: - - Demilitarization: Yes - demil/mli	3.000 inches	
Overall Width: 1.250 inches Operating Tempurature Range: -30.0/+71.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Rende Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug sternal Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 3. solder lug external Connection Type And Quantity: 1 receptacle, coaxial sternal and 3 solder lug external External Dc Operating Voltage In Volts: 2.4.0 single voltage Sheft Life: Na Unit Of Measure:	Overall Height:	
1.250 inches Operating Tempurature Range: -30.0/+71.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Na Uni Of Measure: Periodin Contact Type Periodin Contact	1.000 inches	
Operating Tempurature Range: -30.0/+71.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Clicuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: Na Unit of Measure: - Penillitarization: Yes - demil/mil	Overall Width:	
Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug ront Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: - - Demilitarization: Yes - demil/mli Fig:	1.250 inches	
Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Deprating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Control Type: Remote Control Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Din Of Measure: - Demilitarization: Yes - demil/mli Fig:	Operating Tempurature Range:	
No raid Basic Shape Style: Rectangular or square Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	-30.0/+71.0 degrees celsius	
Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Clicuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shiff Life: N/a Unit Of Measure: Periode: Demilitarization: Yes - demil/mli	Average Life Measurement:	
Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Gircuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Not rated	
Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Fig:	Basic Shape Style:	
Encased Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Sheff Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Rectangular or square	
Operating Control Method: Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit of Measure: Demilitarization: Yes - demil/mli Fig:	Inclosure Type:	
Automatic Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Encased	
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Operating Control Method:	
Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Automatic	
Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Installation Design:	
Remote Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Mechanical	
Circuit Construction Type: Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Control Type:	
Solid state Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Remote	
Frequency Per Channel: 3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: - Pemilitarization: Yes - demil/mli Fig:	Circuit Construction Type:	
3.6 gigahertz operating channel and 6.0 gigahertz operating channel Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Solid state	
Connection Type And Location: Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Frequency Per Channel:	
Receptacle, coaxial front and solder lug front Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	3.6 gigahertz operating channel and 6.0 gigahertz operating channel	
Connection Contact Type And Quantity: 1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Connection Type And Location:	
1 receptacle, coaxial external and 3 solder lug external External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Receptacle, coaxial front and solder lug front	
External Dc Operating Voltage In Volts: 24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Connection Contact Type And Quantity:	
24.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1 receptacle, coaxial external and 3 solder lug external	
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	External Dc Operating Voltage In Volts:	
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	24.0 single voltage	
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:	
 Demilitarization: Yes - demil/mli Fiig:	N/a	
Yes - demil/mli Fiig:	Unit Of Measure:	
Yes - demil/mli Fiig:	-	
Fiig:	Demilitarization:	
-	Yes - demil/mli	
A32200	Fiig:	
	A32200	