Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-371-3736

Inclosure Material:	
Plastic	
Overall Length: 0.820 inches	
Overall Height:	
0.425 inches	
Overall Width:	
0.520 inches	
Environmental Protection:	
Shock resistant and vibration	
Vibration Resistance Range In Hertz:	
+55.0/+200.0	
Vibration Resistance Amplitude:	
35.0 gravitational units	
Shock Resistance Rating In Gravitational Units:	
100.0	
Operating Tempurature Range:	
+0.0/+70.0 degrees celsius	
Storage Tempurature Range:	
-55.0/+125.0 degrees celsius	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Inclosure Type:	
Hermetically sealed	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
1.0 megahertz operating channel	
Signal Voltage Rating Per Channel:	
1.400 volts output	
Shock Pulse Duration Time:	
0.1 milliseconds	
Connection Type And Location:	
Pin bottom	

AeroBase Group

## External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

## Precious Material And Location:

Terminal surfaces gold

### **Precious Material:**

Gold

# Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A32200