## NSN 5955-01-371-6806

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-371-6806 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Shock resistant **Shock Resistance Rating In Gravitational Units:** 1000.0 **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 5945-01-363-9030 relay assembly **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 2.097 megahertz operating channel **Signal Voltage Rating Per Channel:** Between 4.463 volts input and 6.038 volts interstage **Shock Pulse Duration Time:** 6.0 milliseconds **Connection Type And Location:** Err-060 glad hand quick disconnect **External Dc Operating Voltage In Volts:** 4.5 single voltage and 6.0 single voltage Shelf Life:

Unit Of Measure:

N/a

## NSN 5955-01-371-6806

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200