Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-371-6806

Overall Length:
0.887 inches
Overall Height:
0.400 inches
Overall Width:
0.540 inches
Environmental Protection:
Shock resistant
Shock Resistance Rating In Gravitational Units:
1000.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
5945-01-363-9030 relay assembly
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
2.097 megahertz operating channel
Signal Voltage Rating Per Channel:
Between 4.463 volts input and 6.038 volts interstage
Shock Pulse Duration Time:
6.0 milliseconds
Connection Type And Location:
Err-060 glad hand quick disconnect
External Dc Operating Voltage In Volts:
4.5 single voltage and 6.0 single voltage
Shelf Life:
N/a
Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200