## NSN 5955-01-372-1189

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-372-1189 **Reliability Indicator:** Not established **Overall Length:** 0.800 inches **Overall Height:** 0.540 inches **Overall Width:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +1.0/+500.0 **Vibration Resistance Amplitude:** 5.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 30.0 **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Manual Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 6.0 megahertz operating channel **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 14 pin external **External Dc Operating Voltage In Volts:** 4.75 single voltage and 5.25 single voltage

Shelf Life:

N/a

## NSN 5955-01-372-1189

Crystal Controlled Oscillator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200