## NSN 5955-01-372-1191

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-372-1191
Inclosure Material:
Plastic
Overall Length:
0.887 inches
Overall Height:
0.400 inches
Overall Width:
0.540 inches
Environmental Protection:
Shock resistant and vibration
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
6625-01-260-2936 verifier, memory loader
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
112.0 kilohertz operating channel
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
14 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Test Data Document:
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-o-55310/16 government specification

## NSN 5955-01-372-1191

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200