Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-373-5773

Reliability Indicator:
Not established
Overall Length:
2.000 inches
Overall Height:
0.750 inches
Overall Width:
2.000 inches
Environmental Protection:
Shock resistant and vibration
Shock Resistance Rating In Gravitational Units:
30.0
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
4935-01-251-3692 test set, guided missile system
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
180.0 kilohertz operating channel
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
5 pin external
External Dc Operating Voltage In Volts:
14.25 single voltage and 15.75 single voltage

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200