Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-374-2018

| Reliability Indicator: |
|---|
| Not established |
| Inclosure Material: |
| Plastic |
| Overall Length: |
| 1.000 inches |
| Overall Height: |
| 0.090 inches |
| Overall Width: |
| Between 0.605 inches and 0.645 inches |
| Environmental Protection: |
| Shock resistant and vibration |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Control Type: |
| Remote |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 24.0 megahertz operating channel |
| Connection Type And Location: |
| Pin left side and pin right side |
| Connection Contact Type And Quantity: |
| 20 pin external |
| External Dc Operating Voltage In Volts: |
| 4.75 single voltage and 5.25 single voltage |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Nuclear hardness critical item |

Crystal Controlled Oscillator - Page 2 of 2



Precious Material And Location:

Cover surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200