

NSN 5955-01-374-2019 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-374-2019 **Reliability Indicator:** Not established **Overall Length:** 0.500 inches **Overall Height:** 0.385 inches **Overall Width:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Vibration Resistance Amplitude:** 35.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:**

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

12.0 kilohertz operating channel

Shock Pulse Duration Time:

0.35 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

8 pin external

NSN 5955-01-374-2019

Noncrystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200