## NSN 5955-01-374-6004

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-374-6004

Overall Length:
0.815 inches
Overall Height:
Between 0.460 inches and 0.500 inches
Overall Width:
0.515 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Vibration Resistance Amplitude:
35.0 gravitational units
Shock Resistance Rating In Gravitational Units:
1000.0
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
18.432 megahertz operating channel
Shock Pulse Duration Time:
0.35 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Shelf Life:
N/a

N/a

## NSN 5955-01-374-6004

Crystal Controlled Oscillator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200