NSN 5955-01-374-7965

Crystal Controlled Oscillator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-01-374-7965 |
|--|
| Reliability Indicator: |
| Not established |
| Inclosure Material: |
| Plastic |
| Overall Length: |
| 0.887 inches |
| Overall Height: |
| 0.400 inches |
| Overall Width: |
| 0.540 inches |
| Environmental Protection: |
| Shock resistant and vibration |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -62.0/+125.0 degrees celsius |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Hermetically sealed |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Control Type: |
| Remote |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 33.1776 megahertz operating channel |
| Connection Type And Location: |
| Err-060 glad hand quick disconnect |
| Connection Contact Type And Quantity: |
| 14 liters of liquid nitrogen drain |
| External Dc Operating Voltage In Volts: |
| 4.5 single voltage and 5.5 single voltage |
| Test Data Document: |
| 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-o-55310/16 government specification

NSN 5955-01-374-7965

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200