Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-375-9283

Reliability Indicator:
Not established
Overall Length:
2.160 inches
Overall Height:
0.880 inches
Overall Width:
2.000 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+1.0/+500.0
Vibration Resistance Amplitude:
5.0 gravitational units
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
+15.0/+32.0 degrees celsius
Storage Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
7.681692 megahertz operating channel
Frequency Adjustment Type:
Continuous
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Pin bottom

Crystal Controlled Oscillator - Page 2 of 2



Connection Contact Type And Quantity:

5 pin external

External Dc Operating Voltage In Volts:

11.4 single voltage and 12.6 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200