Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-381-5270

•	
	all Length:
	7 inches
	all Height:
) inches
Over	all Width:
) inches
Oper	ating Tempurature Range:
-55.0	/+125.0 degrees celsius
Stora	age Tempurature Range:
-62.0	/+125.0 degrees celsius
Aver	age Life Measurement:
Not r	ated
Basi	c Shape Style:
Recta	angular or square
Inclo	sure Type:
Herm	netically sealed
Oper	ating Control Method:
Auto	natic
Insta	Ilation Design:
Modu	le
Cont	rol Type:
Rem	ote
Circu	uit Construction Type:
Solid	state
Freq	uency Per Channel:
53.0	megahertz operating channel
Con	nection Type And Location:
Err-0	60 glad hand quick disconnect
Conr	nection Contact Type And Quantity:
14 lit	ers of liquid nitrogen drain
Exte	rnal Dc Operating Voltage In Volts:
4.5 క	single voltage and 5.5 single voltage
	Data Document:
	9-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
	at; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	onmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	ification Data:
	9-mil-o-55310/16 government specification
	f Life:
N/a	
	Of Measure:
	ilitarization:
	· demil/mli
162.	

NSN 5955-01-381-5270

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

