NSN 5955-01-385-4332

Vibration Resistance Range In Hertz:

Vibration Resistance Amplitude:

Overall Length: 0.185 inches

Overall Diameter:

0.362 inches

+10.0/+2000.0

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-385-4332

10.0 gravitational units
Shock Resistance Rating In Gravitational Units:
1000.0
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
5895-01-304-8689
Basic Shape Style:
Cylindrical
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
10.0 kilohertz operating channel
Shock Pulse Duration Time:
1.0 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
3 pin external
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Special Features:
Lead length 0.500 in. Min
Precious Material And Location:
External surfaces gold

NSN 5955-01-385-4332

Crystal Controlled Oscillator - Page 2 of 2



Precious Mat	erial:
--------------	--------

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200