# NSN 5955-01-390-7740

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-390-7740

**Overall Length:** 

0.530 inches

**Terminal Length:** 

0.5003 inches

## Overall Width:

0.435 inches

## Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

## **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

### Mode Of Oscillation:

Fundamental

### **Circuit Resonance:**

Series resonance

## Shunt Capacitance In Picofarads:

7.0

### Specified Frequency:

11.000 megahertz

## Holder Cover Material:

Metal or glass

## Operating Tempurature Range:

-55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius

### **End Application:**

5895-01-174-0272

## Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

## **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005 and -0.0010/+0.0010

### **Equivalent Resistance Value In Ohms:**

25.0

## Style Designator:

Rectangular body, pin terminals

## **Test Data Document:**

81349-mil-c-3098g specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/38 government specification

# NSN 5955-01-390-7740

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

