

View Online at <https://aerobasegroup.com/nsn/5955-01-393-2036>

**Overall Length:**

Between 0.496 inches and 0.520 inches

**Overall Height:**

Between 0.185 inches and 0.209 inches

**Overall Width:**

0.197 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

32.0

**Shunt Capacitance In Picofarads:**

7.0

**Specified Frequency:**

24.000 megahertz

**Holder Cover Material:**

Plastic

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**End Application:**

Cmlsa, cma-2000, cage 90073

**Center To Center Distance Between Terminals:**

0.370 inches

**Drive Level Rating:**

0.1 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.005/+0.005

**Second Center To Center Distance Between Terminals:**

0.141 inches

**Equivalent Resistance Value In Ohms:**

50.0

**Style Designator:**

Rectangular body, surface mount

**Test Data Document:**

90073-238-601039-var drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Specification Data:**

90073-238-601039-002 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A059a0