

View Online at <https://aerobasegroup.com/nsn/5955-01-393-2036>

Overall Length:

Between 0.496 inches and 0.520 inches

Overall Height:

Between 0.185 inches and 0.209 inches

Overall Width:

0.197 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

32.0

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

24.000 megahertz

Holder Cover Material:

Plastic

Operating Temperature Range:

-40.0/+85.0 degrees celsius

End Application:

Cmlsa, cma-2000, cage 90073

Center To Center Distance Between Terminals:

0.370 inches

Drive Level Rating:

0.1 milliwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.005/+0.005

Second Center To Center Distance Between Terminals:

0.141 inches

Equivalent Resistance Value In Ohms:

50.0

Style Designator:

Rectangular body, surface mount

Test Data Document:

90073-238-601039-var drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Data:

90073-238-601039-002 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A059a0