

View Online at <https://aerobasegroup.com/nsn/5955-01-393-7895>

Overall Length:

0.265 inches

Terminal Length:

0.600 inches

Diameter:

0.325 inches

Overall Diameter:

0.420 inches

Terminal Diameter:

Between 0.016 inches and 0.029 inches

Mode Of Oscillation:

Third overtone

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

20.0

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

53.000 megahertz

Holder Cover Material:

Metal

Operating Temperature Range:

-45.0/+85.0 degrees celsius

End Application:

5895-01-288-6340

Center To Center Distance Between Terminals:

0.200 inches

Drive Level Rating:

Between 240.0 microwatts and 1000.0 microwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.005/+0.005

Equivalent Resistance Value In Ohms:

40.0

Style Designator:

Hat type, 3 wire leads

Test Data Document:

80063-a3110450 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Data:

80063-a3110450-001 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A059a0