
Crystal Controlled Oscillator - Page 1 of 2





Overall Length: 0.887 inches Overall Height: 0.200 inches Overall Width:

0.540 inches

Operating Tempurature Range:

-55.0/+105.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

Ov-95/tps-73, cage 03950

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

16.55172 megahertz operating channel

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

14 pin external

External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Test Data Document:

81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-o-55310/16 government specification

Shelf Life:

N/a

Unit Of Measure:

D - ----

Demilitarization:

Yes - demil/mli

NSN 5955-01-398-1253

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

