NSN 5955-01-413-7313

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-413-7313 **Overall Length:** Between 0.465 inches and 0.495 inches **Overall Height:** 0.085 inches Overall Width: Between 0.465 inches and 0.495 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** C10661b/aas38 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 56.000 megahertz operating channel **Connection Type And Location:** Pin front and pin left side and pin rear and pin right side **Connection Contact Type And Quantity:** 40 pin external **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-o-55310/19 government specification Shelf Life: N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5955-01-413-7313 Crystal Controlled Oscillator - Page 2 of 2



Fiig:

A32200