Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-413-8624

Overall Length:

Between 0.605 inches and 0.645 inches

Overall Height:

0.090 inches

Overall Width:

0.370 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

An/bqq-5e tac, cage 52088

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

32.000 megahertz operating channel

Connection Type And Location:

Pin left side and pin right side

Connection Contact Type And Quantity:

20 pin external

External Dc Operating Voltage In Volts:

4.85 single voltage and 5.15 single voltage

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

03640-6135298 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Data:

03640-6135298-6 manufacturers source control

Shelf Life:

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200