## NSN 5955-01-417-2130

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-417-2130 **Overall Length:** Between 0.605 inches and 0.645 inches **Overall Height:** 0.090 inches **Overall Width:** 0.370 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Valve-selecti, cage 70339 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state **Frequency Per Channel:** 20.000 megahertz operating channel **Connection Type And Location:** Pin left side and pin right side **Connection Contact Type And Quantity:** 20 pin external **External Dc Operating Voltage In Volts:** 4.75 single voltage and 5.25 single voltage **Criticality Code Justification:** Feat **Special Features:** Nuclear hardness critical item **Nuclear Hardness Critical Feature:** Hardened **Precious Material And Location:** Cover plating gold **Precious Material:** 

Gold

## NSN 5955-01-417-2130

Crystal Controlled Oscillator - Page 2 of 2



## **Test Data Document:**

03640-152a097 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Specification Data:**

03640-152a097-1 manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A32200