# NSN 5955-01-418-2457

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-418-2457

### **Overall Length:**

0.530 inches

**Terminal Length:** 

0.5003 inches

## Overall Width:

0.435 inches

#### Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

#### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

#### Load Capacitance In Picofarads:

Between 29.5 and 30.5

## Shunt Capacitance In Picofarads:

7.0

#### **Specified Frequency:**

5.040 megahertz

#### Holder Cover Material:

Metal or glass

### **Operating Tempurature Range:**

-40.0/+90.0 degrees celsius and -55.0/-40.0 degrees celsius and +90.0/+105.0 degrees celsius

### **End Application:**

Contdrol conso, cage 00136

### **Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

### Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.004/+0.004

## Equivalent Resistance Value In Ohms:

75.0

# Style Designator:

Rectangular body, pin terminals

# **Test Data Document:**

91349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5955-01-418-2457

Quartz Crystal Unit - Page 2 of 2



**Specification Data:** 

81349-mil-c-3098/47 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0