Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-418-2460

Overall Length:
0.887 inches
Overall Height:
0.200 inches
Overall Width:
0.540 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Missile warni, cage 30003
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
2.048 megahertz operating channel
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
14 pin external
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Test Data Document:
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-o-55310/18 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5955-01-418-2460 Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

