NSN 5955-01-421-1350

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-421-1350

| Overall Length: |
|--|
| 0.530 inches |
| Terminal Length: |
| 0.5003 inches |
| Overall Width: |
| 0.435 inches |
| Body Width: |
| 0.402 inches |
| Body Thickness: |
| 0.150 inches |
| Overall Thickness: |
| 0.183 inches |
| Terminal Diameter: |
| Between 0.016 inches and 0.019 inches |
| Mode Of Oscillation: |
| Fundamental |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| Between 2.0 and 3.0 |
| Specified Frequency: |
| 10.000000 megahertz |
| Holder Cover Material: |
| Metal or glass |
| Operating Tempurature Range: |
| -40.0/+70.0 degrees celsius |
| End Application: |
| An/aww-9/9a, cage 30003 |
| Center To Center Distance Between Terminals: |
| 0.184 mils and 0.200 centimeters |
| Drive Level Rating: |
| Between 100.0 microwatts and 1.0 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.0024/+0.0024 and -0.0030/+0.0030 and -0.0050/+0.0050 |
| Equivalent Resistance Value In Ohms: |
| 25.0 |
| Style Designator: |
| Rectangular body, pin terminals |
| Test Data Document: |
| 30003-1064as488 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |

Specification Data:30003-1064as488-1 manufacturers specification

NSN 5955-01-421-1350

Quartz Crystal Unit - Page 2 of 2



| She | lf | I if | ρ. |
|-----|-----|------|----|
| ~ | ••• | | • |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0