Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-423-5252

Overall Length:
0.820 inches
Overall Height:
0.245 inches
Overall Width:
0.520 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Cp-1716a/tpx-, cage 64694
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
50000.0 feet
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
41.424 megahertz operating channel
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Test Data Document:
64694-503150 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Specification Data:
64694-503150-6 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5955-01-423-5252

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

No

Fiig:

A32200