Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-423-7462

## **Overall Length:** 1.400 inches **Overall Diameter:** 2.000 inches **Operating Tempurature Range:** -54.0/+85.0 degrees celsius Average Life Measurement: Not rated **End Application:** E-3 esm grp b, cage 32562 **Basic Shape Style:** Cylindrical **Maximum Operating Altitude Rating:** 30000.0 feet **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Remote **Circuit Construction Type:** Solid state **Frequency Per Channel:** 8.0 gigahertz operating channel and 18.0 gigahertz operating channel **Connection Type And Location:** Pin bottom and receptacle, coaxial bottom **Connection Contact Type And Quantity:** 8 pin external and 1 receptacle, coaxial external **External Dc Operating Voltage In Volts:** 14.8 single voltage and 15.2 single voltage **Test Data Document:** 32562-4000-41005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Specification Data:** 32562-4000-41005-01 manufacturers specification Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

## NSN 5955-01-423-7462

Noncrystal Controlled Oscillator - Page 2 of 2

**Fiig:** A32200

