NSN 5955-01-446-8801

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-446-8801 **Overall Length:** 0.480 inches **Overall Height:** 0.085 inches Overall Width: 0.480 inches **Environmental Protection:** Moisture proof **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Radar warning system, litton systems inc, model an/anl-68 (v) -3 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 3.6 megahertz operating channel **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 40 pin external **External Dc Operating Voltage In Volts:** 5.0 single voltage **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data:

81349-mil-o-55310/19 government specification

Shelf Life:

N/a

NSN 5955-01-446-8801

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200