Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-447-9140

Overall Length: 1.400 inches Overall Diameter: 2.000 inches Operating Tempurature Range: -54.0/+85.0 degrees celsius Average Life Measurement:

Not rated

End Application:

E-3 esm grp b, cage 32562

Basic Shape Style:

Cylindrical

Maximum Operating Altitude Rating:

30000.0 feet

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

8.0 gigahertz operating channel and 18.0 gigahertz operating channel

Connection Type And Location:

Pin bottom and receptacle, coaxial bottom

Connection Contact Type And Quantity:

8 pin external and 1 receptacle, coaxial external

External Dc Operating Voltage In Volts:

14.8 single voltage and 15.2 single voltage

Test Data Document:

32562-4000-41005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Data:

32562-4000-41005-01 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5955-01-447-9140

Noncrystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

