## NSN 5955-01-457-1693

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-457-1693
Overall Length:
0.778 inches
Terminal Length:
0.248 inches
Overall Width:
0.435 inches
Body Length:
0.530 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
0.040 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
52.58333 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+90.0 degrees celsius
Center To Center Distance Between Terminals:
0.192 inches
Drive Level Rating:
1.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.002/+0.002
Equivalent Resistance Value In Ohms:
50.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-mil-prf-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-3098/60 government specification

## NSN 5955-01-457-1693

Quartz Crystal Unit - Page 2 of 2



-			 	
•	hΔ	Iŧ.	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

Mil-std (military Standard):

Mil-prf-3098 spec.