# NSN 5955-01-457-1697

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-457-1697

# **Overall Length:**

1.023 inches

# **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.757 inches

#### **Body Length:**

0.775 inches

#### **Body Width:**

0.725 inches

#### Body Thickness:

0.317 inches

#### **Overall Thickness:**

0.352 inches

#### Terminal Diameter:

Between 0.075 inches and 0.141 inches

## Mode Of Oscillation:

Third overtone

#### **Circuit Resonance:**

Series resonance

# Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

34.8375 megahertz

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

+70.0/+80.0 degrees celsius

## Center To Center Distance Between Terminals:

0.486 inches

## **Drive Level Rating:**

1.0 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

## **Equivalent Resistance Value In Ohms:**

40.0

# Style Designator:

Oval body, pin terminals

## **Test Data Document:**

81349-mil-prf-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-3098/43 government specification

# NSN 5955-01-457-1697

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

# Mil-std (military Standard):

Mil-prf-3098 spec.

