Crystal Controlled Oscillator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-468-5120

| Overall Length:                                |
|--|
| 14.0 millimeters                               |
| Overall Height:                                |
| 4.7 millimeters                                |
| Overall Width:                                 |
| 9.8 millimeters                                |
| Environmental Protection:                      |
| Shock resistant                                |
| Operating Tempurature Range:                   |
| -20.0/+70.0 degrees celsius                    |
| Average Life Measurement:                      |
| Not rated                                      |
| Basic Shape Style:                             |
| Rectangular or square                          |
| Inclosure Type:                                |
| Encased  |
| Installation Design:                           |
| Module   |
| Circuit Construction Type:                     |
| Solid state                                    |
| Frequency Per Channel:                         |
| 60.0 megahertz operating channel               |
| Signal Voltage Rating Per Channel:             |
| 0.400 volts output                             |
| Connection Type And Location:                  |
| Solder lug left side and solder lug right side |
| Connection Contact Type And Quantity:          |
| 4 solder lug external                          |
| External Dc Operating Voltage In Volts:        |
| 4.5 single voltage and 5.5 single voltage      |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |
|  |
| Demilitarization:                              |
| Yes - demil/mli                                |
| Fiig:  |
| A32200   |
|  |
|  |