Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-480-9494

Overall Length:
0.887 inches
Overall Height:
0.400 inches
Overall Width:
0.540 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Operating Tempurature Range:
-28.0/+85.0 degrees celsius
Storage Tempurature Range:
-62.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
5895-01-127-8134
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
12000.0 feet
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
40.000 megahertz operating channel
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
14 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
4.75 single voltage and 5.25 single voltage
Shelf Life:
N/a
Unit Of Measure:

---

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200